


HOLE LEGEND		
DRILLED OR PUNCHED HOLE	HOLE DIA.	TOL.
	0.135 to 0.125	± .003
	.126 to .250	± .004
	.251 to .500	± .005
IDENT.	DESCRIPTION	QTY.
A		

REV.	DATE	DESCRIPTION
1	5/14/71	PER EGM #2149 ADDED FXDX CKT, ADDED 5223 CABLE CONN. ADDED NOTE FOR MODEL 500 APP. R.T.

5223 CABLE CONN.

A0	(A) 1	A3
A5	(B) 2	FXDX
A2	(C) 3	A1
A4	(D) 4	8
1	(E) 5	9
0	(F) 6	RT DC
5	(H) 7	A7
	(J) 8	A6
	(K) 9	A14
2	(L) 10	A13
4	(M) 11	A15
6	(N) 12	A12
7	(P) 13	A11
3	(R) 14	A10
AB	(S) 15	A9



PIN	CONNECTION	SIGN TUBE
1	NUMERAL 1	-
2	"	2
3	"	3
4	"	4
5	"	5
6	"	6 +
7	ANODE	ANODE
8	NUMERAL 7	
9	"	8
10	ANODE	
11	NUMERAL 9	
12	"	0
13	RT. DC. PT.	RT. DC. PT.
14	LT. DC. PT.	

TUBE TYPE	WANG. NO.	QTY.
SIGN	340-0010	2
NUMERAL	340-0011	14

WANG PART NO.	ITEM	QTY.	NAME	MATERIAL	DESCRIPTION
MODEL NO. 700/500 SEE ENGRG SPECIFICATIONS					
TOL. EX. AS NOTED .XX ± .010 FRAC. ± 1/64 .XXX ± .005 ANG. ± 1°30' FINISH V					
SCALE 1/4" = 1" SHT OF					
TITLE SCHEMATIC LOGIBLOC # 5936 NIXIE DISPLAY					
D 5936-1 1					

D 5936-1